



Spot-in Blending Thinner

CM0110510

DESCRIPTION

CM0110510 is a vinyl thinner solvent used for burn-in and outer edge blending of spot-in repairs: (Jet Glo® / Acry Glo®, Conventional and High Solids) This method is used when full panel repair is not possible due to time constraints etc.

Refer to:

- ***Sherwin Williams Jet-Glo & Acry-Glo material fade out technique data sheet***
- ***Farecla polishing technique data sheet for successful topcoat gloss recovery.***

COATING PROPERTIES

	<u>Base Component</u>
Wt./Gal.	7.5 lbs
Sp. Gravity	0.90
V.O.C.	7.5 lbs./gal (899 g/L)

SHELF LIFE

Shelf Life is applicable only for material stored in unopened and undamaged original factory filled containers.

Minimum Storage Temp. 40°F / 4°C

Maximum Storage Temp. 90°F / 32°C

CM0110510: 7 years

PRODUCT INFORMATION

Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.