



PRODUCT INFORMATION SHEET

Jet Glo[®]/Acry Glo[®] H.S. Accelerator CM08181HR

DESCRIPTION

CM08181HR is a universal accelerator for use in both Jet Glo[®] and Acry Glo[®] High Solids.

Advantages:

- Improves drying times of Jet Glo[®] and Acry Glo[®] High Solids.
- Environmentally friendly – 0.0 VOC product.

Great care should be taken when using this product. High levels of CM08181HR Accelerator can result in a reduced potlife, gloss loss, and blistering.

COATING PROPERTIES

Weight Per Gallon:	8.9 lbs.
Sp. Gravity	1.068
VOC:	0.0 lb/gal. (0 g/L)

MIXING INSTRUCTIONS

Jet Glo[®] High Solids

Accelerator for Jet Glo[®] High Solids should be used for touch up parts or small panel areas only.

- 1) Admix product according to Jet Glo[®] High Solids mixing instructions.
- 2) If using 810 series colors, add CM08181HR up to the following levels:

Admixed Quart:	1 ounce
Admixed Pint:	½ ounce

- 3) If using 820 series colors, add CM08181HR up to the following levels:

Admixed Quart:	½ ounce
Admixed Pint:	¼ ounce

Acry Glo[®] High Solids

- 1) Admix product according to Acry Glo[®] High Solids mixing instructions.
- 2) Add CM08181HR up to the following levels:

Admixed Gallon:	1 ounce
Admixed Quart:	¼ ounce

SHELF LIFE

Shelf Life is applicable only for materials stored in unopened and undamaged original factory filled containers.

Minimum Storage Temp. 40°F / 4°C
Maximum Storage Temp. 90°F / 32°C

CM08181HR: 3 years

USE OF SYSTEMS STATEMENT

Jet Glo[®] or Acry Glo[®] High Solids should only be accelerated with CM08181HR Accelerator. CM08181HR is the only product approved for use as an Accelerator with Jet Glo[®] and Acry Glo[®] High Solids.

HEALTH AND SAFETY INFORMATION

Consult the Material Safety Data Sheets for product information regarding health, physical and environmental hazards, handling precautions and "First Responder" first-aid recommendations.

PRODUCT INFORMATION

Please contact your Sherwin-Williams Aerospace Distributor or Representative for more information.

NOTE: Product Information Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Information Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.