



**Model Number:** 2100-956SR  
**Size:** 7-1/4" H x 4-3/4" W x 1-7/8" D  
**Style:** Stainless Steel, Surface Mount  
**Option:** Strobe Interface & Relay



**Model Number:** 2100-956SRM  
**Size:** 7-1/4" H x 4-3/4" W x 1-7/8" D  
**Style:** Stainless Steel, Surface Mount, Mushroom Push Button  
**Option:** Strobe Interface & Relay



**Model Number:** 2100-956RR  
**Size:** 7-1/4" H x 4-3/4" W x 1-7/8" D  
**Style:** Red, Powder Coated, Surface Mount  
**Options:** Strobe Interface & Relay, Mushroom Push Button



**Model Number:** 2100-984LR  
**Size:** 9-7/8" H x 6-5/8" W x 3-1/4" D  
**Style:** Red, NEMA 4, Fiberglass, Exterior Rated  
**Options:** Strobe Interface & Relay, Mushroom Push Button



**Model Number:** 2100-958NSR  
**Face Plate Size:** 9-1/2" H x 7-1/2" W  
**Back Box Size:** 8" H x 6" W x 3" D  
**Style:** Brushed Stainless Steel, Flush Mount  
**Options:** Strobe Interface & Relay, Mushroom Push Button



**Model Number:** 2100-984LRC1  
**Call Box Size:** 9-7/8" H x 6-5/8" W x 3-1/4" D  
**Cover Size:** 6-2/5" H x 3-3/4" W x 2-1/4" D  
**Style:** Red, NEMA 4, Fiberglass, Exterior Rated  
**Option:** Strobe Interface & Relay



**Model Number:** 2100-956SSRC2  
**Face Plate Size:** 10" H x 6-17/25" W  
**Back Box Size:** 9-7/8" H x 6-1/2" W x 3" D  
**Cover Size:** 9-3/4" H x 6-1/2" W x 1-1/4" D  
**Style:** Stainless Steel, Surface Mount  
**Option:** Strobe Interface & Relay



**Model Number:** 2100-958SSRC2  
**Face Plate Size:** 11-3/8" H x 8" W  
**Back Box Size:** 9-7/8" H x 6-1/2" W x 3" D  
**Cover Size:** 9-3/4" H x 6-1/2" W x 1-1/4" D  
**Style:** Brushed Stainless Steel, Flush Mount  
**Option:** Strobe Interface & Relay



**Model Number:** 2100-958NMBR  
**Face Plate Size:** 9-1/2" H x 7-1/2" W  
**Back Box Size:** 8" H x 6" W x 3" D  
**Style:** Antique Bronze, Flush Mount  
**Options:** Strobe Interface & Relay, Mushroom Push Button

### Features:

- Meets all IBC, ADAAG, and NFPA code requirements
- Requires analog telephone line (POTS, PBX, or central office line)
- Power Requirements: 24vdc from model 2500-PWR24U
- 7.2V 300mAH battery (part # RP7300110)
- Built-in battery backup recharges from 24vdc power (allows for a minimum of 4 hours of talk time upon power loss)
- Built-in 10 phone consolidator feature allows you to install 10 Call Boxes and 1 Base Station on a single telephone line
- Programmable with up to 5 emergency numbers
- On-site keypad programming or remote programming
- Remote or on-site diagnostic test
- Recordable location message (18 seconds)
- Automatic dialer (31 digit programmable memory)
- Phone checks every 24 hours for an active phone line, if one is not detected, phone will provide a relay trip
- Compatible with SmartRescue Base Station or Command Center for in-building rescue coordination
- Automatic answer feature with audible ring
- Touch Tone operation only (Touch Tone is an AT&T registered trademark)
- 3 year warranty
- Conforms to UL Standard 2017 for Attendant Monitored Signaling Devices
- Complies with Section 6.4 of UL 60950-1
- ETL Listing Number: 5013373