

**Electric
Cordless**

Swagers



Arm swaging tools and arm oval sleeves must be used in combination set.

Making rigging wire rope, dia. 6mm - 12mm (1/4" - 1/2")

Electric

HS12-120V / HS12-230V

Electric Swager (Hydraulic function)

Swaging Speed : 4seconds



Double insulation



Size : 433mm(W) X 104mm(D) X 243mm(H)

Accessories

Carry Case



Each size of dies



Shoulder Strap

Screwdriver
for replacing die

Wire rope cutter RC-450
Cutting capacity dia. 12mm(1/2")
fiber core wire rope



Gauge
to ensure swaging



Cordless

HS12-MH120 / HS12-MH230

Cordless Swager (Hydraulic function)

Swaging Speed : 7seconds



Battery Output: 14.4V



Size : 355mm(W) X 90mm(D) X 350mm(H)

Accessories

Carry Case



Nickel-Metal Hydride
Battery (Ni-MH)

DC14.4V
3000mAh



Each size of dies



Battery charger
AC120V(HS12-MH120)



Battery charger
AC230V(HS12-MH230)



Gauge
to ensure swaging



Shoulder Strap

Wire rope cutter RC-450
Cutting capacity dia. 12mm(1/2")
fiber core wire rope



Screwdriver
for replacing die

Suitable Sleeve & Dies Swaging times per fully charged battery				Spare Products			
Wire rope Dia. mm (inch)	Oval Sleeve	Suitable Dies	HS12-MH120 HS12-MH230 Swaging times	Product Name	Item No.	Weight	
6 (1/4")	OS-6A	OS-6D	144 times	Dies [6mm (1/4")]	OS-6D	0.5kg	
8 (5/16")	OS-8A	OS-8D	108 times	Dies [8mm (5/16")]	OS-8D	0.5kg	
9 (3/8")	OS-9A	OS-9D&10D	75 times	Dies [9mm (3/8"), 10mm (13/32")]	OS-9D&10D	0.5kg	
10 (13/32")	OS-10A	OS-9D&10D	75 times	Dies [12mm (1/2")]	OS-12D	0.5kg	
12 (1/2")	OS-12A	OS-12D	39 times	Nickel-Metal Hydride Battery	PHT-EB1430H	0.8kg	
				Battery charger [120V]	UC18YRL	0.7kg	
				Battery charger [230V]	UC18YRL	0.7kg	




Output pressure

HS12-120V / HS12-230V : 11tonf
HS12-MH120 / HS12-MH230 : 10tonf
Safety-valve will be automatically operated, when the pressure is over 10tonf or


Head turns around

Head turns 180 degrees in 45 degrees steps.

Swaging position



3 point swaging



Item No.	Electrical input	Electricity	Wire rope dia. mm (inch)	Weight	Packing weight	M 3
HS12-120V	AC120V	7.0A	6, 8, 9, 10, 12	7.5kg	18kg	0.056
HS12-230V	AC230V	3.6A	(1/4", 5/16", 3/8", 13/32", 1/2")			
Item No.	Battery / Electrical input	Charging time	Wire rope dia. mm (inch)	Weight	Packing weight	M 3
HS12-MH120	14.4V 3000mAh(Ni-MH) / AC120V	45 minutes	6, 8, 9, 10, 12	6.5kg	15.5kg	0.063
HS12-MH230	14.4V 3000mAh(Ni-MH) / AC230V		(1/4", 5/16", 3/8", 13/32", 1/2")			

WESTECH RIGGING SUPPLY
Call Toll Free: 800-442-7475

Call Us or Visit Our Stores:
Monday - Friday, 8:00am - 5:30pm Pacific



Visit Us Online at: www.WestechRigging.com

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302