


Wire Rope Thimbles

Heavy Duty Thimbles Hot Dipped Galvanized


Rope Diameter	Weight per 100 pcs (lbs)	Dimensions			
		A	B	C	D
1/4	7	2.19	1.62	1.50	.88
5/16	12	2.50	1.88	1.81	1.06
3/8	22	2.88	2.12	2.12	1.12
7/16	35	3.25	2.38	2.38	1.25
1/2 - 9/16	51	3.62	2.75	2.75	1.50
5/8	76	4.25	3.25	3.12	1.75
3/4	158	5.00	3.75	3.81	2.00
7/8	177	5.50	4.25	4.25	2.25
1	313	6.12	4.50	4.75	2.50
1-1/8 - 1-1/4	400	7.00	5.12	5.88	2.88
1-1/4 - 1-3/8	811	9.08	6.50	6.81	3.50
1-3/8 - 1-1/2	1,294	9.00	6.25	7.12	3.50
1-5/8	1,700	11.25	8.00	8.12	4.00
1-3/4	1,775	12.19	9.00	8.50	4.50
1-7/8 - 2	2,775	15.12	12.00	10.38	6.00



Meets Federal Spec FF-T-276b, Type III

Standard Thimbles Hot Dipped Galvanized

Rope Diameter (in)	Weight per 100 pcs (lbs)	Dimensions			
		A	B	C	D
1/8	2.00	1.94	1.31	1.06	.69
3/16	2.70	1.94	1.31	1.06	.69
1/4	3.50	1.94	1.31	1.06	.69
5/16	3.60	2.13	1.50	1.25	.81
3/8	5.80	2.38	1.63	1.47	.94
7/16	10.00	2.47	1.71	1.62	1.03
1/2	11.60	2.75	1.88	1.75	1.13
5/8	32.00	3.50	2.25	2.38	1.38
3/4	49.00	3.75	2.50	2.69	1.63
7/8	83.00	5.00	3.50	3.19	1.88
1	94.00	5.69	4.25	3.75	2.50
1-1/8 - 1-1/4	175.00	6.25	4.50	4.31	2.75



Meets Federal Spec FF-T-276b, Type II