

QUICK REFERENCE CARD

Minimum number of PCC Tiedowns required to secure an article against movement based on D.O.T. Weight Only requirements. Also meets C.V.S.A. guidelines.



Weight of Load - Multiply by 1000 lbs.

Size / W.L.L.		5	10	15	20	25	30	35	40	45	50
		2" /3,000 lbs.	1	2	3	4	5	5	6	7	8
2" /3,335 lbs.		1	2	3	3	4	5	6	6	7	8
3" /4,000 lbs.		1	2	2	3	4	4	5	5	6	7
3" /5,000 lbs.		1	1	2	2	3	3	4	4	5	5
4" /5,000 lbs.		1	1	2	2	3	3	4	4	5	5

D.O.T. requirements and C.V.S.A. guidelines state the aggregate static working load limit (W.L.L.) of the tiedown assemblies used to secure an article against movement in any direction must be equal to at least 1/2 (.5) times the weight of the article. Additional tiedown assemblies may be required to meet industry, local, state and federal regulations. **Warning: Do not exceed working load limits. Do not use tiedown straps for overhead lifting.**

Distributed By

WESTECH RIGGING SUPPLY

Visit Us Online at: www.WestechRigging.com

Call Us Toll Free at: 800-442-7475

Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302

