



U.S. Door & Building Components Roll-Up Doors Ideal For Commercial Applications

Features	Benefits	Models			
		536	601	651	652
General	Light-duty commercial applications	Standard			
	Heavy duty commercial applications		Standard		
	Commercial wind load application				Standard
	Heavy duty commercial wind load application			Standard	
	Sizes up to 12' wide by 12' high.	Standard			
	9-1/2" drum for minimal headroom applications	Standard			
	12" drum for a smoother operation of larger doors		Standard	Standard	Standard
	Sizes up to 16' wide by 16' high.		Standard		
Sizes up to 20' wide by 16' high.				Standard	Standard
Adjustable Tension Device	Allows for EZ Spring adjustment	Standard	Optional	Optional	Optional
Counter Balance- 2 5/8" Spring	Heavy gauge spring has been tested to withstand over 80,000 cycles.	Standard	Standard	Standard	Standard
	Factory lubricated, heat treated and pre-stretched for low friction resulting in maintenance-free operation.	Standard	Standard	Standard	Standard
Chain Hoist	Reduced drive shaft chain hoist fits in limited sideroom applications.	Standard doors over 100 sq. ft.	Optional		
	Reduced drive chain hoist creates ease of operation even in larger doors (over 100 square feet).	Optional	Standard doors over 100 sq. ft.	Standard doors over 100 sq. ft.	Standard doors over 100 sq. ft.
	Both types can be locked for additional security.	Standard	Standard	Standard	Standard
Electric Operators	Three different models available to fit your specific application.	Optional	Optional	Optional	Optional
Insulation	Laminated foil bubble type insulation is built into the doors during the manufacturing process providing a thermal barrier.	Optional	Optional	Optional	Optional
Mounting Brackets	Heavy gauge embossed stamped steel	Standard			
	Welded structural steel angle brackets		Standard	Standard	Standard
Axle	Fixed axle -1" diameter shaft assembled inside galvanized barrel assembly	Standard			
	Heavy duty fixed axle- 1 5/16" diameter shaft assembled inside galvanized barrel assembly		Standard	Standard	Standard
Head Stop	Heavy gauge door stop provides positive stop every time.	Standard	Standard	Standard	Standard
Bottom Bar	Two-part posi-lock door stop system for additional safety.	Standard	Standard	Standard	Standard
	Galvalume acrylic coated to stand up to the elements.	Standard	Standard	Standard	Standard
	Reinforced with galvanized steel angle with PVC bulb astragal to create a full seal with the floor.	Standard	Standard	Standard	Standard
Paint Finish	Siliconized polyester	Standard	Standard	Standard	Standard
	Chalk and fade resistant	Standard	Standard	Standard	Standard
	20 year limited warranty against chalking and fading	Standard	Standard	Standard	Standard
Guides	Guides are universal making them suitable for mounting to any style jamb. Feature permanently attached polypropylene wear strip eliminating friction and sharp edges.	Standard	Standard	Standard	Standard
	18 gauge galvanized steel	Standard			
	16 gauge galvanized steel		Standard		Standard
	14 gauge galvanized steel		Optional	Standard	
Vinyl Wear Strip	Smooth surface for quieter operation.	Standard	Standard		
	Interior wear strip insures quiet, nest-free operation over the lifetime of the door.	Standard	Standard	Standard	Standard
Barrel Assembly	Protects paint by properly spacing sheets apart when the door is open.	Standard	Standard	Standard	Standard
	Radial steel bearings provide longevity and ease of operation.	Standard	Standard	Standard	Standard
Packaging	Doors are individually suspended by the axles during shipment preventing door to door contact. Each door is foam wrapped then stretch wrapped to insure factory fresh delivery to your job site and protection from the elements.	Standard	Standard	Standard	Standard
	Doors are packaged in recyclable pallets and boxes.	Standard	Standard	Standard	Standard
	Optional suspended packaging available for less than truckload quantities. Ideal for distribution centers.	Optional	Optional	Optional	Optional
Wind Load Ratings	For wind loads in excess of 120mph we offer UHM nylon windlocks which provides quieter, smoother operation than traditional windlocks and install with ease.				Standard
	Steel wind locks for wind loads in excess of 122mph. Doors can be configured to meet tough Miami-Dade County codes.			Standard	
Locks	Bottom bar inside lock made from heavy gauge galvanized steel.	Standard	Standard	Standard	Standard
	Padlock can be added for additional security.				
	Mini-lock	Optional	Optional	Optional	Optional